

HP - Spray Gun KSP 3000

Z 5-1 e

electrically operated (without mechanical valve)

01.05.2010

- HP - Gun complete with spray tube 750 mm, hose connector M 14x1.5 LH, Initiator with 2m cable (for remote control) and nozzle holder for insert nozzles (without nozzle)

Part No. 7018125



Additional equipment

- Shoulder support
- Half shell handle
- Handle

Part No. 7009215

Part No. 7009921

Part No. 7001071



Technical data

Max. working pressure:	3000 bar
Max. capacity:	40 l/min
Connection:	M 26x1.5 female (with pressure screw M 26x1.5 and pressure ring M 14x1.5 LH)
Total length:	1000 mm
Weight:	approx. 3.0 kg
Temperature:	max. 50°C
Usable nozzle inserts:	Insert nozzles Type 0952 (see page Z 45-1 e) Rotating nozzle PRD 3000 (see page Z 20-1 e) Rotating nozzle PRD 3000 Air (see page Z 30-1 e) Orbital nozzle KOD 2500 (see page Z 40-1/2/3/4 e)

Applications

For manual surface cleaning of all type of forms and materials with nozzle.



For hand-held operation of a spray gun the nozzle diameter must be selected to ensure that the reaction force in the longitudinal axis when used at the max. operating pressure does not exceed 250 N. If the reaction force is in excess of 150 N the gun must be equipped with a support, in compliance with the European Norm prEN 1829.