

## High Pressure Hose Lines

2500 / 3000 bar

Z 60-3 e

01.01.2009

### Component group includes:

- Hose line with fitting M14 x 1.5 left hand male
- Hose security
- Protective hose
- See page Z 60-4 e

### Technical data:

- Working pressure: max. 2500 / 3000 bar
- Hose inner layer: Polyoxymethylene (POM)
- Pressure hose section: 6 layers of steel wire of highest tensile strength
- Hose outer layer: Polyamide (PA)
- Fitting: High pressure fitting (steel) with 59° cone



Fitting: M 14 x 1.5 LH					
NW / ID [mm]	NW / ID [mm]	NW / ID [mm]	NW / ID [mm]	NW / ID [mm]	NW / ID [mm]
5	2500 bar	13,4	200	5	7015603
				10	7006367
				15	7006368
				20	7006369
5	3000 bar	15.3	220	20	7000471
8	2500 bar	17,8	260	10	7006370
				15	7006371
				20	7006372
8	3000 bar	19.5	280	20	7000476

Fitting: 9/16" - 18 UNF LH					
NW / ID [mm]	NW / ID [mm]	NW / ID [mm]	NW / ID [mm]	NW / ID [mm]	NW / ID [mm]
12/13	2500 bar	27,7	350	20	7017337