



## High Pressure Hoses

Z 60-1 e

ID 13 - ID 25

01.04.2008

ID [mm]	max. operating pressure	O.D. Ø	Fitting Cap Nut, f	Length [m]	Part No.
10	1400 bar	19,4 mm	M 24x1.5 DKO SW = 30	5	700 2971
				20	700 2972
				40	700 2973
12/13	720 bar	24,6 mm	M 22x1.5 DKL SW = 27	5	700 0490
				20	700 0491
				40	700 0492
	1100 bar	25,4 mm	M 24x1.5 DKO SW = 30	5	700 0494
				10	7009339
				15	7011070
				20	700 0495
	1400 bar	29,5 mm	M 24x1.5 DKO SW = 30	40	700 0496
				5	700 0498
				20	700 0499
	1800 bar	24,5 mm	M 24x1.5 DKO SW = 32	40	700 0500
				5	700 0502
20				700 0503	
40				700 0504	
20	1000 bar	30 mm	M 36x2 DKO SW = 41	5	700 0518
				20	700 0519
				40	700 0520
	1400 bar	33 mm	M 36x2 DKO SW = 41	5	700 2987
				20	700 2988
				40	700 2989
25	750 bar	37 mm	M 42x2 DKO SW = 50	5	700 0530
				20	700 0531
				40	700 0532

Double Nipple + Red. Double Nipple	ID	Pressure	Part No.
M 22x1.5 DKL	13	1000 bar	105 1631
M 22x1.5 DKO	13	1500 bar	7004137
M 24x1.5 DKO	13	1500 bar	105 0671
M 36x2 DKO	20	1500 bar	105 0672
M 42x2 DKO	25	650 bar	504 0190
M 22x1.5 DKL - M 24x1.5 DKO	13	1500 bar	700 1628
M 24x1.5 DKO - M 36x2 DKO	13	1500 bar	105 0673
M 36x2 DKO - M 42x2 DKO	13	1000 bar	105 1709
M 22x1.5 Nose - M 22x1.5 DKL	13	1000 bar	105 0014
M 22x1.5 Nose - M 24x1.5 DKO	13	1500 bar	105 0340
M 22x1.5 Nose - M 36x2 DKO	13	1500 bar	105 0548
M 30x1.5 Nose - M 24x1.5 DKO	20	1500 bar	105 0648
M 30x1.5 Nose - M 36x2 DKO	20	1500 bar	105 0571
M 30x1.5 Nose - M 42x2 DKO	20	1500 bar	105 1726
M 38x1.5 Nose - M 36x2 DKO	25	1000 bar	700 4182
M 38x1.5 Nose - M 42x2 DKO	25	1000 bar	105 1062

Hose safety devices	Hose NW / ID [mm]	Part No.
Steel wire loop and spring system	10 - 20	700 2804
	25	700 2805
Aluminium half-shells	13	700 2806
	20 - 25	700 2807

Further sizes and fitting types are available upon request