

Pipe Cleaning Nozzle

Z 46-1 e

Rigid type

01.04.2008

- To be used on lances and hoses only












Please specify with order:

- Working pressure in bar
- Flow rate in l/min
- Number of bores
- Forward jet yes / no
- Jetting angle



Technische Daten

Max. working pressure: 750 bar
 Material: hardened steel 1.4112

Form	Jetting symbol	Jetting angle		Connection female	Outer Ø [mm]	Length [mm]	Hex.	Part No.
04.01		30°	45°	G 1/8"	12	29	----	2560001
		60°	75°					
04.03		30°	45°	G 1/4"	16	25	----	2560003
		60°	75°					
04.09		15° + 75°		G 1/8"	14	45	10	2560014
04.10		15° + 75°		G 1/4"	16	55	14	2560015
05.01		0 - 90° forward 30 - 90° back		G 1/8"	12	30	10	2560016
05.15		0 - 90° forward 30 - 90° back		M 8	10	30	----	2560068
05.02		0 - 90° forward 30 - 90° back		G 1/4"	16	30	14	2560017
05.03		0 - 90° forward 30 - 90° back		M 22x1.5	28	40	24	2560018
05.08		30° - 45° - 60°		G 1/2"	30	35	24	2560054
05.10		30° - 45° - 60°		G 3/4"	35	40	32	2560056
05.12		30° - 45° - 60°		G 1"	50	60	41	2560058