


Straight Jet Threaded Nozzle Type 0987 + 0965

Z 55-1 e

Round Jet Sapphire Nozzle

01.04.2008

- To be used with Nozzle Heads for Rotating Tools, PRD 3000 and Surface Cleaner



Technical data

Max. working pressure:	3000 bar
Material:	Sapphire inserts made of Al ₂ O ₃ Housing made of cold-formed steel (1.4305)
Sealing by a seal seat	
Secured by hexagon socket	
Nozzle factor:	0.85

Ø [mm]	Operating pressure	Type 0987 - M 8 x 1		Type 0965 - M 10	
		Part No.	L [mm]	Part No.	L [mm]
0,20	max. 3000 bar	7005520	12	7006250	18
0,25		7016274		7006251	
0,30		7005521		7006252	
0,35		7005536		7006253	
0,40		7005522		7006254	
0,45		7005537		7006255	
0,50		7005523		7006256	
0,55		7005538		7011511	
0,60		7005524		7006257	
0,65		-----		7011512	
0,70		7005525		7006258	
0,75		-----		7011465	
0,80		7005526		7006259	
0,85		-----		7011464	
0,90		7005527		7006260	
0,95		-----		7013152	
1,00		7005528		7006424	
Plug		7006249		7006425	